

## Forced Convection Ovens WF-02G



### General Models

Ideal for high temperature storage with user-friendly design.

WF-G Models is used for all sterilization and drying tasks that do not require high drying rates or special time requirements, ideal for drying applications requiring a gentle airflow.

### Operating Features

- From +10°C above room temperature to 260°C .
- Microprocess PID control / Auto-tuning / Calibration.
- Digital timer: 1 min to 59 hr. 59 min, delayed ON / OFF.
- Over temperature limit protection / Door opening alarm.
- Conveniently preset 3 most commonly used temperature settings without auto-tuning.
- Digital LED display (1°C resolution) with touch keypads

## Constructional Features

- Gravity-flow convection with vertical airflow for uniform sample heating.
- Three fold tempered glass viewing window allows for easy monitoring of samples.
- Featuring a pull-down door handle.
- Rounded inner chamber corners for easy cleaning and better air-flowing.
- Stainless-steel interior.
- Two circular adjustable top slide vents help to control inner air vapor circulation. (38mm / 1.5" in dia.)

## Specifications

Model	WF-02G	
Chamber Volume ( L )	50	
Temperature	Range ( °C )	Amb. +10~ 260
	Fluctuation at 100°C ( °C )	0.5
Dimension (W×D×H)	Interior ( mm )	400 × 420 × 420
	Exterior ( mm )	540 × 620 × 780
Number of shelves	2ea (Max shelves 8ea)	
Weight ( kg )	53	
Heating Power ( W )	1000	
Order No.	12155K	

### WIGGENS GmbH

Gässlesweg 22-24, 75334 Straubenhardt, Germany  
Tel.: 0049 7248 4529088

### WIGGENS China

Room 303, Hall C, Office Building M8, No.1 Jiuxianqiao East  
Road, Chaoyang District, Beijing 100015, China  
Tel: +86 400-809-2068  
Fax: +86 400-809-2068-112  
Email: info@wiggens.com service@wiggens.com  
Website: www.wiggens.com